

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes 4" standard ABS inlet

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	1,500 imp. gallons	6,820 litres
Septic volume	1,366 imp. gallons	6,210 litres
Effluent volume	-	-
Overall length	176.4 in	4,480 mm
Approx. weight	461 lbs	209 kg

maintenance.

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

MARKETS & APPLICATIONS



COMMERCIAL



fiberglass pill-style holding tank designed for shallow burial depths up to

0.6m (2ft). The lightweight fiberglass construction provides a durable,

corrosion-resistant, and high-strength structure that requires virtually zero-

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

Ż

CROSS-SECTION OF LAMINATE

AGRICULTURAL

AVAILABLE OPTIONS

- Additional fittings & connections •
- Manway extensions •
- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM FAX: 1.204.233.6938

EMAIL: info@carlsoncomposites.com