

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	1,500 imp. gallons	6,820 litres
Useable volume	1,597 imp. gallons	7,260 litres
Overall length	176.3 in	4,477 mm
Approx. weight	595 lbs	270 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT

LAYER (NEAT RESIN

fiberglass pill-style water tank designed for burial depths up to 2.14m (7ft). The lightweight fiberglass construction provides a durable, corrosionresistant, and high-strength structure that requires virtually zeromaintenance.

STRUCTURAL LAYER (NEAT RESIN) Ż EXTERIOR SURFACE LAYER (GEL COAT) CROSS-SECTION OF LAMINATE

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions •
- Lockable manway cover
- Hinged manway cover
- Double-walled construction •
- Insulated or heat-traced
- NSF potable water lining ٠
- Full customization & engineering







COMMERCIAL



AGRICULTURAL



WWW.CARLSONCOMPOSITES.COM

FAX: 1.204.233.6938