#### CECPIL-1750IG-5P3.05 CARLSON ENGINEEREED OMPOSITES 1750 Gallon Pill Style Pump Out Tank **Product Specifications** 152.5 [3872.4] 63.70 [1618.0] 12.0 Ø30.01.D. [762.0] 303.5 TYF LIFTING -LUG (GLASSED-IN) 914.6 13.3 [336.6] 13.7 [68.4] TYP [347.8] PENETRATION PENETRATION INTO LIQUID INTO LIQUID 104.0 [2656.4] Ø 60.5 Ø 65.9 [1537.0] [1673.8] 49.5 [1257.3] 24.0 D-RING FIBREGLASS 47.5

q

200.0 O.D [5080.3]

X

CROSS-SECTION OF LAMINATE

- [609.6]

TYF

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

The CECPIL-1750IG-5P3.05 product is a CSA-approved 1750 imp. gallon

fiberglass pill-style pump out tank designed for burial depths up to 3.05m

(10ft). The lightweight fiberglass construction provides a durable, corrosion-

resistant, and high-strength structure that requires virtually zero-

\_\_\_\_\_

## FEATURES AND BENEFITS

CSA certified design and construction

DIVIDER

(GLASSED-IN)

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes 4" standard ABS inlet
- Standard 10-year limited warranty

# KEY SPECIFICATIONS

Nominal volume	1,750 imp. gallons	7,955 litres
Septic volume	1,336 imp. gallons	6,073 litres
Effluent volume	234 imp. gallons	1,063 litres
Overall length	200 in	5,080 mm
Approx. weight	773 lbs	351 kg

maintenance.

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

[1206.5] WORKING CAPACITY

## MARKETS & APPLICATIONS



COMMERCIAL



AGRICULTURAL

## AVAILABLE OPTIONS

Additional fittings & connections •

(GLASSES-IN)

2 PLCS

- Manway extensions •
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM FAX: 1.204.233.6938

EMAIL: info@carlsoncomposites.com