

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection

Includes 4" sta	andard ABS inlet
-----------------	------------------

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	1,750 imp. gallons	7,955 litres
Septic volume	1,336 imp. gallons	6,073 litres
Effluent volume	234 imp. gallons	1,063 litres
Overall length	199.9 in	5,077 mm
Approx. weight	609 lbs	276 kg

maintenance.

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

MARKETS & APPLICATIONS



COMMERCIAL



fiberglass pill-style trickle tank designed for burial depths up to 0.6m (2ft).

The lightweight fiberglass construction provides a durable, corrosion-

resistant, and high-strength structure that requires virtually zero-

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

Ż

CROSS-SECTION OF LAMINATE

AGRICULTURAL

AVAILABLE OPTIONS

- Additional fittings & connections •
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM