

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection 30" wide easy-access manway
- Includes 4" standard ABS inlet
- Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	2,000 imp. gallons	9,092 litres
Septic volume	1,782 imp. Gallons	8,101 litres
Effluent volume	-	-
Overall length	224.4 in	5,077 mm
Approx. weight	770 lbs	349 kg

maintenance.

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

MARKETS & APPLICATIONS



COMMERCIAL



fiberglass pill-style holding tank designed for burial depths up to 2.14m (7ft).

The lightweight fiberglass construction provides a durable, corrosion-

resistant, and high-strength structure that requires virtually zero-

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

X

CROSS-SECTION OF LAMINATE

AGRICULTURAL

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions •
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM

PHONE: 1.204.233.0671

FAX: 1.204.233.6938