

## FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

External gelcoat for increased protection
30" wide easy-access manway

Includes	4" standa	rd ABS inlet	

Standard 10-year limited warranty

## KEY SPECIFICATIONS

Nominal volume	10,000 imp. gallons	45,460 litres
Septic volume	9,989 imp. gallons	45,411 litres
Effluent volume	-	-
Overall length	289.7 in	7,358 mm
Approx. weight	1,897 lbs	860 kg

## MARKETS & APPLICATIONS



durable, corrosion-resistant, and high-strength structure that requires virtually zero-maintenance. STRUCTURAL LAYER INTERIOR (NEAT RESIN) X

AGRICULTURAL

imp. gallon fiberglass pill-style holding tank designed for burial depths up to

0.6m (2ft). The lightweight filament wound fiberglass construction provides a

ANTI-WICKING LAYER (NEAT RESIN) INTERIOR EXTERIOR SURFACE CHEMICAL-RESISTANT LAYER (NEAT RESIN LAYER (GEL COAT) CROSS-SECTION OF LAMINATE

## AVAILABLE OPTIONS

- Additional fittings & connections •
- Manway extensions •
- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



COMMERCIAL

