

requires virtually zero-maintenance.

X

CROSS-SECTION OF LAMINATE

## FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

External gelcoat for increased protection
---

- 30" wide easy-access manway
- Includes 4" standard ABS inlet

Standard 10-year limited warranty

## KEY SPECIFICATIONS

Nominal volume	10,000 imp. gallons	45,460 litres
Septic volume	8,622 imp. gallons	39,196 litres
Effluent volume	1,366 imp. gallons	6,210 litres
Overall length	289.7 in	7,358 mm
Approx. weight	2,029 lbs	920 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

## MARKETS & APPLICATIONS



COMMERCIAL



AGRICULTURAL

imp. gallon fiberglass pill-style pumpout tank designed for burial depths up

to 0.6m (2ft). The lightweight filament wound fiberglass construction

provides a durable, corrosion-resistant, and high-strength structure that

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

## AVAILABLE OPTIONS

- Additional fittings & connections •
- Manway extensions •
- ٠ Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM FAX: 1.204.233.6938

EMAIL: info@carlsoncomposites.com