

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes standard bulkhead outlet drain
- Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	11,000 imp. gallons	50,000 litres
Septic volume	9,625 imp. gallons	43,756 litres
Effluent volume	1,366 imp. gallons	6,210 litres
Overall length	318.0 in	8,077 mm
Approx. weight	3,075 lbs	1,395 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

MARKETS & APPLICATIONS









11000 imp. gallon fiberglass pill-style pumpout tank designed for burial

depths up to 2.14m (7ft). The lightweight filament wound fiberglass

construction provides a durable, corrosion-resistant, and high-strength

structure that requires virtually zero-maintenance.

Ł

CROSS-SECTION OF LAMINATE

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AGRICULTURAL

AVAILABLE OPTIONS

- Additional fittings & connections ٠
- Manway extensions •
- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM