

requires virtually zero-maintenance.

Ż

CROSS-SECTION OF LAMINATE

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes standard bulkhead outlet drain
- Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	11,000 imp. gallons	50,000 litres
Septic volume	11,003 imp. gallons	50,021 litres
Effluent volume	-	-
Overall length	287.5 in	7,303 mm
Approx. weight	2,740 lbs	1,243 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

MARKETS & APPLICATIONS



COMMERCIAL



AGRICULTURAL

11000 imp. gallon fiberglass pill-style water tank designed for burial depths

up to 2.14m (7ft). The lightweight filament wound fiberglass construction

provides a durable, corrosion-resistant, and high-strength structure that

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AVAILABLE OPTIONS

- Additional fittings & connections •
- Manway extensions •
- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM FAX: 1.204.233.6938

EMAIL: info@carlsoncomposites.com