

## FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

External gelcoat for increased protection
30" wide easy-access manway

Includes 4" standard ABS inlet

KEY SPECIFICATIONS

Nominal volume

Septic volume

**Effluent volume** 

**Overall length** 

Approx. weight

## Standard 10-year limited warranty

## X EXTERIOR SURFACE CHEMICAL-RESISTANT LAYER (GEL COAT)

CROSS-SECTION OF LAMINATE

virtually zero-maintenance.

_	AVAILABLE OPTIONS	
•	Additional fittings & connections	

- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



MARKETS & APPLICATIONS





INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

LAYER (NEAT RESIN

12,000 imp. gallons

11,995 imp. gallons

344.7 in

2,214 lbs



The CECPIL-12000IG-10H.6 product is an 10-ft diameter CSA-certified 12000

imp. gallon fiberglass pill-style holding tank designed for burial depths up to

0.6m (2ft). The lightweight filament wound fiberglass construction provides a

durable, corrosion-resistant, and high-strength structure that requires

STRUCTURAL LAYER

54,550 litres

54,530 litres

8,755 mm

1,004 kg

(NEAT RESIN)

AGRICULTURAL

COMMERCIAL

WWW.CARLSONCOMPOSITES.COM FAX: 1.204.233.6938

EMAIL: info@carlsoncomposites.com