

## FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes standard bulkhead outlet drain
- Standard 10-year limited warranty

## KEY SPECIFICATIONS

Nominal volume	12,000 imp. gallons	54,550 litres
Septic volume	11,995 imp. gallons	54,530 litres
Effluent volume	-	-
Overall length	345.5 in	8,776 mm
Approx. weight	3,128 lbs	1,419 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

## MARKETS & APPLICATIONS









12000 imp. gallon fiberglass pill-style holding tank designed for burial

depths up to 2.14m (7ft). The lightweight filament wound fiberglass

construction provides a durable, corrosion-resistant, and high-strength

\_\_\_\_\_

structure that requires virtually zero-maintenance.

X

CROSS-SECTION OF LAMINATE

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

## AVAILABLE OPTIONS

- Additional fittings & connections ٠
- Manway extensions •
- ٠ Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM