

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

External gelcoat for increased protection
30" wide easy-access manway

Includes 4" standard ABS inlet

KEY SPECIFICATIONS

Nominal volume

Septic volume


Effluent volume

Overall length

Approx. weight

Standard 10-year limited warranty

The CECPIL-12000IG-10P.6 product is an 10-ft diameter CSA-certified 12000 imp. gallon fiberglass pill-style pumpout tank designed for burial depths up to 0.6m (2ft). The lightweight filament wound fiberglass construction provides a durable, corrosion-resistant, and high-strength structure that requires virtually zero-maintenance.



ΑVΑ	ILAB	LE OP	TIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering







12,000 imp. gallons

10,628 imp. gallons

1,366 imp. gallons

344.7 in

2,347 lbs





A GRICUL TURAL

54,550 litres

48,316 litres

6.210 litres

8,755 mm

1,065 kg



PHONE: 1.204.233.0671

WWW.CARLSONCOMPOSITES.COM