

## FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes standard bulkhead outlet drain
- Standard 10-year limited warranty

## KEY SPECIFICATIONS

Nominal volume	12,000 imp. gallons	54,550 litres
Septic volume	10,628 imp. gallons	48,316 litres
Effluent volume	1,366 imp. gallons	6,210 litres
Overall length	345.5 in	8,776 mm
Approx. weight	3,260 lbs	1,479 kg

INTERIOR

INTERIOR

ANTI-WICKING LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

## MARKETS & APPLICATIONS









12000 imp. gallon fiberglass pill-style pumpout tank designed for burial

depths up to 2.14m (7ft). The lightweight filament wound fiberglass

construction provides a durable, corrosion-resistant, and high-strength

structure that requires virtually zero-maintenance.

X

CROSS-SECTION OF LAMINATE

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

## AGRICULTURAL

Δ	VA	ILA	BLE	OP	TIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM