

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

30" wide easy-access manway

Includes 4" standard ABS inlet

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	12,500 imp. gallons	59,826 litres	
Septic volume	11,138 imp. gallons	50,634 litres	
Effluent volume	1,366 imp. gallons	6,210 litres	
Overall length	358.7 in	9,111 mm	
Approx. weight	2,397 lbs	1,087 kg	

INTERIOR

INTERIOR

ANTI-WICKING


LAYER (NEAT RESIN

MARKETS & APPLICATIONS





COMMERCIAL



STRUCTURAL LAYER

requires virtually zero-maintenance.

The CECPIL-12500IG-10P.6 product is an 10-ft diameter CSA-certified 12500

imp. gallon fiberglass pill-style pumpout tank designed for burial depths up

to 0.6m (2ft). The lightweight filament wound fiberglass construction

provides a durable, corrosion-resistant, and high-strength structure that

AV	AIL	ABLE	OPTI	ons

- Additional fittings & connections ٠
- Manway extensions •
- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining ٠
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM

AGRICULTURAL