

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes standard bulkhead outlet drain
- Standard 10-year limited warranty

KEY SPECIFICATIONS

12,500 imp. gallons	56,826 litres
11,138 imp. gallons	50,634 litres
1,366 imp. gallons	6,210 litres
359.5 in	9,131 mm
3,319 lbs	1,505 kg
	11,138 imp. gallons 1,366 imp. gallons 359.5 in

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN)

MARKETS & APPLICATIONS









The CECPIL-12500IG-10P2.14 product is an 10-ft diameter CSA-certified

12500 imp. gallon fiberglass pill-style pumpout tank designed for burial

depths up to 2.14m (7ft). The lightweight filament wound fiberglass

construction provides a durable, corrosion-resistant, and high-strength

structure that requires virtually zero-maintenance.

Ł

CROSS-SECTION OF LAMINATE

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

A GRICUL TURAL

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM