

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

| External gelcoat for increased protection | |
|---|--|
|---|--|

| 30" wide | easy-access | manway |
|----------|-------------|--------|
|----------|-------------|--------|

Includes 4" standard ABS inlet

Standard 10-year limited warranty

KEY SPECIFICATIONS

| Nominal volume | 14,000 imp. gallons | 63,645 litres |
|-----------------|---------------------|---------------|
| Septic volume | 14,000 imp. gallons | 63,645 litres |
| Effluent volume | - | - |
| Overall length | 399.7 in | 10,152 mm |
| Approx. weight | 2,535 lbs | 1,150 kg |

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN)

virtually zero-maintenance.

X

CROSS-SECTION OF LAMINATE

MARKETS & APPLICATIONS



齓

COMMERCIAL



The CECPIL-14000IG-10H.6 product is an 10-ft diameter CSA-certified 14000

imp. gallon fiberglass pill-style holding tank designed for burial depths up to

0.6m (2ft). The lightweight filament wound fiberglass construction provides a

durable, corrosion-resistant, and high-strength structure that requires

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AGRICULTURAL

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM