

structure that requires virtually zero-maintenance.

............

CROSS-SECTION OF LAMINATE

\*

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

## FEATURES AND BENEFITS

CSA certified design and construction		
Corrosion resistant		
100% neat resin construction		
Virtually maintenance-free		
External gelcoat for increased protection		
30" wide easy-access manway		
Includes standard bulkhead outlet drain		

Standard 10-year limited warranty

## KEY SPECIFICATIONS

Nominal volume	14,000 imp. gallons	63,645 litres
Septic volume	14,000 imp. gallons	63,645 litres
Effluent volume	-	-
Overall length	401.0 in	10,185 mm
Approx. weight	5,087 lbs	2,307 kg

INTERIOR

INTERIOR

ANTI-WICKING LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN)

## MARKETS & APPLICATIONS



齓

COMMERCIAL



The CECPIL-14000IG-10H3.66 product is an 10-ft diameter CSA-certified 14000 imp. gallon fiberglass pill-style holding tank designed for burial depths up to 3.66m (12ft). The lightweight filament wound fiberglass construction provides a durable, corrosion-resistant, and high-strength

AGRICULTURAL

## AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM