

structure that requires virtually zero-maintenance.

* * * *

X + + +

* * * * * * * * * * * * *

CROSS-SECTION OF LAMINATE

FEATURES AND BENEFITS

CSA certified design and construction

Corrosion resistant

100% neat resin construction

Virtually maintenance-free

External gelcoat for increased protection

30" wide easy-access manway

Includes standard bulkhead outlet drain

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	14,000 imp. gallons	63,645 litres
Septic volume	12,633 imp. gallons	57,431 litres
Effluent volume	1,366 imp. gallons	6,210 litres
Overall length	400.5 in	10,173 mm
Approx. weight	3,635 lbs	1,649 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT

LAYER (NEAT RESIN)

MARKETS & APPLICATIONS



L.

COMMERCIAL



The CECPIL-14000IG-10P2.14 product is an 10-ft diameter CSA-certified

14000 imp. gallon fiberglass pill-style pumpout tank designed for burial

depths up to 2.14m (7ft). The lightweight filament wound fiberglass

construction provides a durable, corrosion-resistant, and high-strength

(NEAT RESIN)

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

A GRICUL TURAL

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering



PHONE: 1.204.233.0671

WWW.CARLSONCOMPOSITES.COM