

requires virtually zero-maintenance.

* * * * * * * * * * * *

CROSS-SECTION OF LAMINATE

0.00

......

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction

Virtually maintenance-free

External gelcoat for increased protection

30" wide easy-access manway

Includes standard bulkhead outlet drain

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	15,000 imp. gallons	68,191 litres
Septic volume	15,008 imp. gallons	68,228 litres
Effluent volume	-	-
Overall length	386.3 in	9,812 mm
Approx. weight	4,885 lbs	2,216 kg

INTERIOR

INTERIOR

ANTI-WICKING LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN)

MARKETS & APPLICATIONS





COMMERCIAL



The CECPIL-15000IG-10W3.66 product is an 10-ft diameter CSA-certified 15000 imp. gallon fiberglass pill-style water tank designed for burial depths

up to 3.66m (12ft). The lightweight filament wound fiberglass construction

provides a durable, corrosion-resistant, and high-strength structure that

STRUCTURAL LAYER (NEAT RESIN)

EXTERIOR SURFACE

LAYER (GEL COAT)

A GRICUL TURAL

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM