

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway

Includes standard bulkhead outlet drain

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	17,500 imp. gallons	79,557 litres
Septic volume	17,501 imp. gallons	79,561 litres
Effluent volume	•	-
Overall length	496.5 in	12,611 mm
Approx. weight	4,054 lbs	1,839 kg

INTERIOR

ANTI-WICKING LAYER (NEAT RESIN)

CHEMICAL-RESISTANT

LAYER (NEAT RESIN)

MARKETS & APPLICATIONS





COMMERCIAL



structure that requires virtually zero-maintenance.

* * * * * * * * * * * * * *

CROSS-SECTION OF LAMINATE

........

AGRICULTURAL

17500 imp. gallon fiberglass pill-style holding tank designed for burial

depths up to 2.14m (7ft). The lightweight filament wound fiberglass

construction provides a durable, corrosion-resistant, and high-strength

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)



- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- ٠ NSF potable water lining
- Full customization & engineering



PHONE: 1.204.233.0671

WWW.CARLSONCOMPOSITES.COM

FAX: 1.204.233.6938