

structure that requires virtually zero-maintenance.

\* \* \* \*

\* \* \* \* \* \* \* \* \*

\* \* \* \* \* \* \* \* \* \* \* \*

CROSS-SECTION OF LAMINATE

## FEATURES AND BENEFITS

CSA certified design and construction

Corrosion resistant

100% neat resin construction

Virtually maintenance-free

External gelcoat for increased protection

30" wide easy-access manway

Includes standard bulkhead outlet drain

Standard 10-year limited warranty

## KEY SPECIFICATIONS

Nominal volume	20,000 imp. gallons	90,922 litres
Septic volume	17,501 imp. gallons	79,561 litres
Effluent volume	-	-
Overall length	565.0 in	14,351 mm
Approx. weight	4,482 lbs	2,033 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT

LAYER (NEAT RESIN)

## AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering







COMMERCIAL



AGRICULTURAL

The CECPIL-20000IG-10H2.14 product is an 10-ft diameter CSA-certified

20000 imp. gallon fiberglass pill-style holding tank designed for burial

depths up to 2.14m (7ft). The lightweight filament wound fiberglass

construction provides a durable, corrosion-resistant, and high-strength

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)



*шшш.CARLSONCOMPOSITES.COM* FAX: 1.204.233.6938