

structure that requires virtually zero-maintenance.

* * * *

* * * * * * * * *

* * * * * * * * * * * *

CROSS-SECTION OF LAMINATE

FEATURES AND BENEFITS

CSA certified design and construction

Corrosion resistant

100% neat resin construction

Virtually maintenance-free

External gelcoat for increased protection

30" wide easy-access manway

Includes standard bulkhead outlet drain

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	22,500 imp. gallons	102,287 litres
Septic volume	22,496 imp. gallons	102,269 litres
Effluent volume	-	-
Overall length	633.5 in	16,091 mm
Approx. weight	4,912 lbs	2,228 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT

LAYER (NEAT RESIN)

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering







COMMERCIAL



The CECPIL-22500IG-10H2.14 product is an 10-ft diameter CSA-certified

22500 imp. gallon fiberglass pill-style holding tank designed for burial

depths up to 2.14m (7ft). The lightweight filament wound fiberglass construction provides a durable, corrosion-resistant, and high-strength

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

A GRICUL TURAL



WWW.CARLSONCOMPOSITES.COM FAX: 1.204.233.6938

EMAIL: info@carlsoncomposites.com