
CECPIL-22500IG-10P2.14 CARLSON ENGINEEREED COMPOSITES 22500 Gallon Pill Style Pumpout Tank **Product Specifications** 126.0 [3200.4] TYP LIFTING-LUG Ø30.01.0 [762.0] 6.0 [152.4] (GLASSED-IN 2 PLCS 25.3 [641.4] PENETRATION 100.5 120.4 Ø125.7 [2552.7] [3058.4] [3192.6] 134.5 [3415.6] RKING 1524.0 D-RING FIBREGLASS Ģ [457.2 (GLASSED-IN) DIVIDER 2 PLCS (GLASSED-IN) 633.5

[16090.6]

FEATURES AND BENEFITS

CSA certified design and construction Corrosion resistant 100% neat resin construction Virtually maintenance-free External gelcoat for increased protection 30" wide easy-access manway Includes standard bulkhead outlet drain Standard 10-year limited warranty The CECPIL-22500IG-10P2.14 product is an 10-ft diameter CSA-certified 22500 imp. gallon fiberglass pill-style pumpout tank designed for burial depths up to 2.14m (7ft). The lightweight filament wound fiberglass construction provides a durable, corrosion-resistant, and high-strength structure that requires virtually zero-maintenance.



AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering



KEY SPECIFICATIONS

Nominal volume

Septic volume

Effluent volume

Overall length

Approx. weight





COMMERCIAL

22,500 imp. gallons

21,129 imp. gallons

1,366 imp. gallons

633.5 in

5,043 lbs



AGRICULTURAL

102,287 litres

96,054 litres

6,210 litres

16,091 mm

2,287 kg



PHONE: 1.204.233.0671

WWW.CARLSONCOMPOSITES.COM

FAX: 1.204.233.6938