

requires virtually zero-maintenance.

CROSS-SECTION OF LAMINATE

Ż

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway

Includes standard bulkhead outlet drain

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	22,500 imp. gallons	102,287 litres
Septic volume	20,012 imp. gallons	90,976 litres
Effluent volume	-	-
Overall length	569.5 in	14,465 mm
Approx. weight	4,486 lbs	2,035 kg

INTERIOR

INTERIOR

ANTI-WICKING LAYER (NEAT RESIN)

CHEMICAL-RESISTANT

LAYER (NEAT RESIN)

MARKETS & APPLICATIONS





COMMERCIAL



22500 imp. gallon fiberglass pill-style water tank designed for burial depths

up to 2.14m (7ft). The lightweight filament wound fiberglass construction

provides a durable, corrosion-resistant, and high-strength structure that

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AGRICULTURAL

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering



PHONE: 1.204.233.0671

WWW.CARLSONCOMPOSITES.COM