

structure that requires virtually zero-maintenance.

+ + +

Ż

* * * * * * * *

CROSS-SECTION OF LAMINATE

FEATURES AND BENEFITS

CSA certified design and construction

Corrosion resistant

100% neat resin construction

Virtually maintenance-free

External gelcoat for increased protection

30" wide easy-access manway

Includes standard bulkhead outlet drain

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	25,000 imp. gallons	113,652 litres
Septic volume	24,993 imp. gallons	113,620 litres
Effluent volume	-	-
Overall length	702.5 in	17,844 mm
Approx. weight	7,879 lbs	3,574 kg

INTERIOR

INTERIOR

ANTI-WICKING LAYER (NEAT RESIN)

CHEMICAL-RESISTANT

LAYER (NEAT RESIN)

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering

MARKETS & APPLICATIONS





COMMERCIAL



The CECPIL-25000IG-10H3.66 product is an 10-ft diameter CSA-certified

25000 imp. gallon fiberglass pill-style holding tank designed for burial

depths up to 3.66m (12ft). The lightweight filament wound fiberglass construction provides a durable, corrosion-resistant, and high-strength

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AGRICULTURAL



PHONE: 1.204.233.0671

WWW.CARLSONCOMPOSITES.COM