

FEATURES AND BENEFITS

25000 imp. gallon fiberglass pill-style pumpout tank designed for burial CSA certified design and construction depths up to 3.05m (10ft). The lightweight filament wound fiberglass construction provides a durable, corrosion-resistant, and high-strength Corrosion resistant structure that requires virtually zero-maintenance. 100% neat resin construction Virtually maintenance-free INTERIOR External gelcoat for increased protection ANTI-WICKING LAYER (NEAT RESIN) 30" wide easy-access manway INTERIOR Includes 4" standard outlet CHEMICAL-RESISTANT

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	25,000 imp. gallons	113,652 litres
Septic volume	23,626 imp. gallons	107,406 litres
Effluent volume	1,366 imp. gallons	6,210 litres
Overall length	702.3 in	17,838 mm
Approx. weight	6,334 lbs	2,873 kg

LAYER (NEAT RESIN)

AVAILABLE OPTIONS

- Additional fittings & connections ٠
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering







COMMERCIAL



* * * * * * * * * * * * * * * *

CROSS-SECTION OF LAMINATE

+ + +



The CECPIL-25000IG-10P3.05 product is an 10-ft diameter CSA-certified

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AGRICULTURAL



WWW.CARLSONCOMPOSITES.COM

FAX: 1.204.233.6938