

virtually zero-maintenance.

FEATURES AND BENEFITS

CSA certified design and construction

Corrosion resistant

100% neat resin construction

Virtually maintenance-free

External gelcoat for increased protection

30" wide easy-access manway

Includes standard ABS bulkhead outlet

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	25,000 imp. gallons	113,652 litres
Septic volume	25,006 imp. gallons	113,680 litres
Effluent volume	-	-
Overall length	630.2 in	16,007 mm
Approx. weight	3,731 lbs	1,692 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT

LAYER (NEAT RESIN)

AVAILABLE OPTIONS

•	Additional	fittings	&	connections
---	------------	----------	---	-------------

- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering

MARKETS & APPLICATIONS





COMMERCIAL



The CECPIL-25000IG-10W.6 product is an 10-ft diameter CSA-certified 25000

imp. gallon fiberglass pill-style water tank designed for burial depths up to

0.6m (2ft). The lightweight filament wound fiberglass construction provides a

durable, corrosion-resistant, and high-strength structure that requires

* * * * * * * * * * * *

CROSS-SECTION OF LAMINATE

* * * * * * * *

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AGRICULTURAL



WWW.CARLSONCOMPOSITES.COM FAX: 1.204.233.6938

EMAIL: info@carlsoncomposites.com