

## FEATURES AND BENEFITS

- CSA certified design and construction
- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes 4" standard ABS inlet

Standard 10-year limited warranty

## KEY SPECIFICATIONS

Nominal volume	6,000 imp. gallons	27,275 litres
Septic volume	4,851 imp. gallons	22,053 litres
Effluent volume	885 imp. Gallons	4,023 litres
Overall length	278.6 in	7,070 mm
Approx. weight	2,930 lbs	1,329 kg

maintenance.

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN)

## MARKETS & APPLICATIONS









The CECPIL-6000IG-8T2.14 product is an 8-ft diameter CSA-certified 6000

imp. gallon fiberglass pill-style trickle tank designed for burial depths up to

2.14m (7ft). The lightweight fiberglass construction provides a durable,

corrosion-resistant, and high-strength structure that requires virtually zero-

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

Ł

CROSS-SECTION OF LAMINATE

AGRICULTURAL

## AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM