CECPIL-7000IG-10H3.05 CARLSON ENGINEEREED COMPOSITES 7000 Gallon Pill Style Holding Tank **Product Specifications** 58.0 1473.2 60 90 2.7 Ø 30.01.D. [152.4] 67.9 228.6 [762.0] TYP LIFTING-LUG (GLASSED-IN) 134.5 Ø120.5 Ø125.8 [3417.1] 100.5 [3059.9] [3195.7] [2552.7] WORKING CAPACITY 18.0 D-RING [457.2] (GLASSED-IN) G TYP

208.6 5299.5

requires virtually zero-maintenance.

Ż

CROSS-SECTION OF LAMINATE

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes standard bulkhead outlet drain
- Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	7,000 imp. gallons	31,823 litres
Septic volume	7,000 imp. gallons	31,823 litres
Effluent volume	-	-
Overall length	208.6 in	5,298 mm
Approx. weight	2,684 lbs	1,217 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

MARKETS & APPLICATIONS





COMMERCIAL



AGRICULTURAL

AVAILABLE OPTIONS

- Additional fittings & connections ٠
- Manway extensions

2 PLCS

The CECPIL-7000IG-10H3.05 product is an 10-ft diameter CSA-certified 7000

imp. gallon fiberglass pill-style holding tank designed for burial depths up to

3.05m (10ft). The lightweight filament wound fiberglass construction

provides a durable, corrosion-resistant, and high-strength structure that

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM FAX: 1.204.233.6938

EMAIL: info@carlsoncomposites.com