

requires virtually zero-maintenance.

Ż

CROSS-SECTION OF LAMINATE

## FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

External gelcoat for increased protection
30" wide easy-access manway

Includes	4"	standard	ARS	inlet

```
Standard 10-year limited warranty
```

## KEY SPECIFICATIONS

Nominal volume	7,000 imp. gallons	31,823 litres
Septic volume	5,615 imp. gallons	25,526 litres
Effluent volume	1,366 imp. gallons	6,210 litres
Overall length	208.5 in	5,296 mm
Approx. weight	2,408 lbs	1,092 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

## MARKETS & APPLICATIONS









imp. gallon fiberglass pill-style pumpout tank designed for burial depths up

to 2.14m (7ft). The lightweight filament wound fiberglass construction

provides a durable, corrosion-resistant, and high-strength structure that

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AGRICULTURAL

## AVAILABLE OPTIONS

- Additional fittings & connections ٠
- Manway extensions •
- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM