

FEATURES AND BENEFITS

- CSA certified design and construction
- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes 4" standard ABS inlet
- Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	7,000 imp. gallons	31,823 litres
Septic volume	5,776 imp. gallons	26,256 litres
Effluent volume	885 imp gallons	4,023 litres
Overall length	318.6 in	8,092 mm
Approx. weight	3,375 lbs	1,530 kg

maintenance.

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

MARKETS & APPLICATIONS



COMMERCIAL



AGRICULTURAL

The CECPIL-7000IG-8T2.14 product is an 8-ft diameter CSA-certified 7000

imp. gallon fiberglass pill-style trickle tank designed for burial depths up to

2.14m (7ft). The lightweight fiberglass construction provides a durable,

corrosion-resistant, and high-strength structure that requires virtually zero-

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

Ł

CROSS-SECTION OF LAMINATE

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions •
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM FAX: 1.204.233.6938

EMAIL: info@carlsoncomposites.com