

requires virtually zero-maintenance.

Ż

CROSS-SECTION OF LAMINATE

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free
- External gelcoat for increased protection
- 30" wide easy-access manway
- Includes standard bulkhead outlet drain
- Standard 10-year limited warranty

KEY SPECIFICATIONS

| Nominal volume | 7,500 imp. gallons | 34,088 litres |
|-----------------|--------------------|---------------|
| Septic volume | 7,419 imp. gallons | 33,727 litres |
| Effluent volume | - | - |
| Overall length | 220.3 in | 5,596 mm |
| Approx. weight | 3,395 lbs | 1,540 kg |

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

MARKETS & APPLICATIONS



COMMERCIAL



AGRICULTURAL

imp. gallon fiberglass pill-style holding tank designed for burial depths up to

3.66m (12ft). The lightweight filament wound fiberglass construction

provides a durable, corrosion-resistant, and high-strength structure that

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AVAILABLE OPTIONS

- Additional fittings & connections ٠
- Manway extensions
- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM