

requires virtually zero-maintenance.

Ż

CROSS-SECTION OF LAMINATE

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

External gelcoat for increased protection
30" wide easy-access manway

Includes 4" standard ABS inlet
Includes 4 Standard ABS Intel

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	7,500 imp. gallons 34,088 litres			
Septic volume	6,052 imp. gallons	27,513 litres		
Effluent volume	1,366 imp. gallons	6,210 litres		
Overall length	220.0 in	5,588 mm		
Approx. weight	2,537 lbs	1,151 kg		

INTERIOR

INTERIOR

ANTI-WICKING LAYER (NEAT RESIN)

CHEMICAL-RESISTANT

LAYER (NEAT RESIN

MARKETS & APPLICATIONS









imp. gallon fiberglass pill-style pumpout tank designed for burial depths up

to 2.14m (7ft). The lightweight filament wound fiberglass construction

provides a durable, corrosion-resistant, and high-strength structure that

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AGRICULTURAL

Δ	VA	ILL	BLE	OP	TIO	NS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM