

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

External gelcoat for increased protection

30" wide	easy-access	manway
----------	-------------	--------

Includes 4" standard ABS inlet

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	7,500 imp. gallons	34,088 litres
Septic volume	6,238 imp. gallons	28,358 litres
Effluent volume	885 imp. Gallons	4,023 litres
Overall length	338.6 in	8,600 mm
Approx. weight	3,669 lbs	1,664 kg

maintenance.

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN)

MARKETS & APPLICATIONS



L.

COMMERCIAL



The CECPIL-7500IG-8P2.14 product is an 8-ft diameter CSA-certified 7500

imp. gallon fiberglass pill-style pumpout tank designed for burial depths up

to 2.14m (7ft). The lightweight fiberglass construction provides a durable,

corrosion-resistant, and high-strength structure that requires virtually zero-

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

X

CROSS-SECTION OF LAMINATE

AGRICULTURAL

AVAILABLE OPTIONS

- Additional fittings & connections
- Manway extensions
- Lockable manway cover
- Hinged manway cover
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM

FAX: 1.204.233.6938