

FEATURES AND BENEFITS

CSA certified design and construction

- Corrosion resistant
- 100% neat resin construction
- Virtually maintenance-free

External gelcoat for increased protection

30" wide e	easy-access	manway
------------	-------------	--------

Standard 10-year limited warranty

KEY SPECIFICATIONS

Nominal volume	8,000 imp. gallons	36,370 litres
Septic volume	7,419 imp. gallons	33,727 litres
Effluent volume	-	-
Overall length	236.0 in	5,994 mm
Approx. weight	2,458 lbs	1,115 kg

INTERIOR

INTERIOR

ANTI-WICKING

LAYER (NEAT RESIN)

CHEMICAL-RESISTANT LAYER (NEAT RESIN

virtually zero-maintenance.

Ż

CROSS-SECTION OF LAMINATE

MARKETS & APPLICATIONS



COMMERCIAL



imp. gallon fiberglass pill-style holding tank designed for burial depths up to

2.14m (7ft). The lightweight filament wound fiberglass construction provides

a durable, corrosion-resistant, and high-strength structure that requires

STRUCTURAL LAYER

EXTERIOR SURFACE

LAYER (GEL COAT)

(NEAT RESIN)

AGRICULTURAL

AVAILABLE OPTIONS

- Additional fittings & connections ٠
- Manway extensions •
- Lockable manway cover
- Hinged manway cover •
- Polylok effluent filter
- Double-walled construction
- Insulated or heat-traced •
- NSF potable water lining
- Full customization & engineering



WWW.CARLSONCOMPOSITES.COM